

Summary specifications



Panel Specifications:

Panel length: 48" and 96"
Panel weight: 8.2 lbs and 16.4 lbs
Panel width: 15-1/4" overall / 15" usable face
Panel area: 5 sq ft and 10 sq ft
Panel thickness: 11/16"

Slot Specifications:

Slot spacing: 3.0" on center
Slot groove: .200"
Slot lip: .375"
Slot opening: .375"

HangUp Specifications:

HangUp Dim: 2" long x 3/4" high x 1/2" thick
HangUp spacing: 3.0"
HangUp Angle: 45 degrees

Fire Rating / Flame Spread:

IIB / 45-775

Loading:

Distance from Panel Face

	4"	6"	8"	10"	12"	14"	16"	
storeWALL	148	125	110	88	70	52	35	lbs per
HeavyDuty								bracket

Shipping Specifications:

4' carton

HeavyDuty

panel quantity: 6 pcs
total area coverage: 30 sq ft / 2.78 m²
carton weight: 60 lbs / 27 kg
carton dim: 49.5" x 16" x 4.375"
125 cm x 40 cm x 11 cm

8' carton

HeavyDuty

panel quantity: 4 pcs
total area coverage: 40 sq ft / 3.7 m²
carton weight: 76 lbs / 34 kg
carton dim: 97.5" x 16" x 3.375"
247 cm x 40 cm x 9 cm

Specifications result of in-house and/or certified independent laboratory testing to ANSI, ISO, or ASTM protocols and standards.